

DIAMOND

Gelato Showcase

STANDARD FEATURES

- Available heights 46"H, 54"H, and 59"H
- Chrome finishing
- LED lighting on shelf
- Electric control board
- Electric defrost
- Front glass with safely tilt down opening system
- Dixell control
- 10° incline deck
- Illuminated flavor panel
- Pyrolytic anti-fog front and side glass
- Cases ship standard unfinished

OPTIONS

- Remote condensing unit
- Stainless steel or acrylic pans
- Round tubs
- RAL color/laminate front and side panels
- Casters
- Popsicle display tray (stainless steel & plastic.
- Plastic available in color options (see images on the bottom)



| DIAMOND GELATO | | | | | | | |
|--|-------------------|--|--|--|--|--|--|
| TECHNICAL FEATURES | | MODELS | | | | | |
| | | DIAMOND 2 G1110 | DIAMOND 2 G1610 | DIAMOND 2 G2106 | DIAMOND 2 G2106 Dual Temp | DIAMOND 2 GA30 | DIAMOND 2 GC30 |
| External Dimensions (L-D-H) | Inches | * 44" - 44 3/16" - 53 3/4" | * 63 11/16" - 44 3/16" - 53 3/4" | * 83 1/4" - 44 3/16" - 53 3/4" | * 83 1/4" - 44 3/16" - 53 3/4" | * 63" - 44 3/16" - 53 3/4" | * 39 1/2" - 44 3/16" - 53 3/4" |
| | MM | 1118 - 1122 - 1366 | 1618 - 1122 - 1366 | 2114 - 1122 - 1366 | 2114 - 1122 - 1366 | 1601 - 1122 - 1366 | 1003 - 1122 - 1366 |
| Crated Dimensions (L-D-H) | Inches | 52" - 52" - 61" | 70" - 52" - 61" | 90" - 52" - 61" | 90" - 52" - 61" | 70" - 52" - 61" | 46" - 52" - 61" |
| | MM | 1320 - 1320 - 1549 | 1778 - 1320 - 1549 | 2286 - 1320 - 1549 | 2286 - 1320 - 1549 | 1778 - 1320 - 1549 | 1168 - 1320 - 1549 |
| 5 Liter Pan Capacity* | Pan Configuration | | | | | | |
| 14 3/16" x 6 1/2" x 4 3/4" (360mm x 165mm x 120mm) | | | | | | | |
| 8 Liter Pan Capacity* | Pan Configuration | | | | | | |
| 14 3/16" x 9 13/16" x 4 3/4" (360mm x 250mm x 120mm) | | | | | | | |
| Refrigeration | Type | Fan Ventilated | Fan Ventilated | Fan Ventilated | Fan Ventilated | Fan Ventilated | Fan Ventilated |
| Refrigeration Display Area | Type | Deck | Deck | Deck | Deck | Deck | Deck |
| Operating Temperature | °C / °F | -18°C / -0.4°F | -18°C / -0.4°F | -18°C / -0.4°F | (2) -18°C / -0.4°F | -18°C / -0.4°F | -18°C / -0.4°F |
| Compressor | Nr./Type | 1 / Semi-Hermetic | 1 / Semi-Hermetic | 1 / Semi-Hermetic | 2 / Semi-Hermetic | 1 / Semi-Hermetic | 1 / Semi-Hermetic |
| BTU'S @ -25°F Evap Temperature (Remote) | BTU'S | 2450 BTU'S | 3580 BTU'S | 4550 BTU'S | 1520 BTU'S + 2520 BTU'S | 3610 BTU'S | 3610 BTU'S |
| Electric Supply | (V/Ph/Hz) | 400/3/50 +N (UE) 208-220/3/60Hz (USA) | 400/3/50 +N (UE) 208-220/3/60Hz (USA) | 400/3/50 +N (UE) 208-220/3/60Hz (USA) | 400/3/50 +N (UE) 208-220/3/60Hz (USA) | 400/3/50 +N (UE) 208-220/1/60Hz (USA) | 400/3/50 +N (UE) 208-220/1/60Hz (USA) |
| Power Consumption | (W/A) | 1950W / 5.2A | 3030W / 8.4A | 3620W / 9.4A | 3700W / 9.5A | 2820W / 7.2A | 2780W / 6.9A |
| Defrost | Mode/Type | Reverse Cycle | Reverse Cycle | Reverse Cycle | Reverse Cycle | Reverse Cycle | Reverse Cycle |
| Climatic Class | N°/°C/°F°/H.R. | 4+/35/95/70% | 4+/35/95/70% | 4+/35/95/70% | 4+/35/95/70% | 4+/35/95/70% | 4+/35/95/70% |
| Refrigerant Gas | Type | R404A | R404A | R404A | R404A | R404A | R404A |
| Net Weights | Kg/Lb | 255Kgs / 562Lbs | 327Kgs / 720Lbs | 410Kgs / 903Lbs | 415Kgs / 914Lbs | 295Kgs / 650Lbs | 295Kgs / 650Lbs |
| Crated Weights | Kg/Lb | 365Kgs / 804Lbs | 477Kgs / 1051Lbs | 610Kgs / 1344Lbs | 615Kgs / 1355Lbs | 455Kgs / 981Lbs | 455Kgs / 981Lbs |

* Dimensions are without side panels & with Diamond 2 technical features * Pans not Included

* Manufacturer reserves the right to change specifications without notice. Not responsible for error and omissions.



361-367 Beach Road, Burlingame, CA 94010
 Tel: 855.885.2400 | 650.342.2400 | Fax: 650.342.7400
 sales@oscartek.com | www.oscartek.com



