

### STANDARD FEATURES


- LED lighting system
- Extra clear glass upper structure
- Sliding plexiglass doors
- Stainless steel lower interior foam tub
- Galvanized chassis structure
- All tempered glass
- Cases ship standard unfinished

### OPTIONS

- Cold storage
- Remote condensing unit
- Casters
- RAL color/laminate front and side panels
- Available in matching Gelato case



PHOTO SHOWN MATCHING GELATO



GEM S3 DELI/PASTRY							
TECHNICAL FEATURES		MODELS					
		GEM S3 DP1000	GEM S3 DP1300	GEM S3 DP1500	GEM S3 DP1700	GEM S3 DP2000	GEM S3 DPA90
External Dimensions (L-D-H)	Inches	39 1/4" - 34 1/4" - 55"	51 1/4" - 34 1/4" - 55"	59" - 34 1/4" - 55"	67" - 34 1/4" - 55"	78 3/4" - 34 1/4" - 55"	78 3/16" - 34 1/4" - 55"
	Inches-MM	1000 - 869 - 1400	1300 - 869 - 1400	1500 - 869 - 1400	1700 - 869 - 1400	2000 - 869 - 1400	1986 - 869 - 1400
Crated Dimensions (L-D-H)	Inches	45" - 40" - 61"	59" - 40" - 61"	67" - 40" - 61"	74 3/4" - 40" - 61"	84" - 40" - 61"	84" - 40" - 61"
	Inches-MM	1150 - 1016 - 1549	1500 - 1016 - 1549	1700 - 1016 - 1549	1900 - 1016 - 1549	2150 - 1016 - 1549	2150 - 1016 - 1549
Refrigeration	Type	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
Refrigeration Display Area	Type	Deck	Deck	Deck	Deck	Deck	Deck
Operating Temperature	°F	40°F	40°F	40°F	40°F	40°F	40°F
Compressor	Nr./Type	Hermetic	Hermetic	Hermetic	Hermetic	Hermetic	Hermetic
BTU'S @ +14°F Evap	BTU'S	1900 BTU'S	2400 BTU'S	3600 BTU'S	3800 BTU'S	3100 BTU'S	3100 BTU'S
Electric Supply	(V/Ph/Hz)	120/1/60	120/1/60	120/1/60	120/1/60	120/1/60	120/1/60
Power Consumption	(A)	8A	10A	11A	12A	14A	13A
Defrost	Mode/Type	Air	Air	Air	Air	Air	Air
Refrigerant Gas	Type	R404A	R404A	R404A	R404A	R404A	R404A
Net Weights	Kg/Lb	120Kgs / 264Lbs	135Kgs / 298Lbs	158Kgs / 348Lbs	187Kgs / 412Lbs	202Kgs / 445Lbs	151Kgs / 333Lbs
Crated Weights	Kg/Lb	150Kgs / 330Lbs	165Kgs / 364Lbs	180Kgs / 388Lbs	217Kgs / 478Lbs	235Kgs / 518Lbs	200Kgs / 420Lbs

\* Dimensions are without side panels



361-367 Beach Road, Burlingame, CA 94010  
 Tel: 855.885.2400 | 650.342.2400 | Fax: 650.342.7400  
 sales@oscartek.com | www.oscartek.com

