



STANDARD FEATURES

- Matches with Metro & Metro II line
- LED lighting top canopy & top shelf
- LED lighting on lower canopy & intermediate shelf
- Lift up double pane hydraulic front glass
- Hermetic air cooled condensing unit
- Forced air refrigeration
- Cold top deck option
- Front, top and side double glasses
- Adjustable legs
- Dixell control with diagnostic
- Cases ship standard unfinished

OPTIONS

- Self-rolling night curtain
- Condensate water tray with automatic evaporating system
- S/s steps for display area
- Hot glass shelves with electric control
- Remote condensing unit
- RAL color/laminate front and side panels
- Casters

METRO COMBI			
TECHNICAL FEATURES		MODELS	
		METRO MCOMBI1150	METRO MCOMBI1650
External Dimensions (L-D-H)	Inches	45 1/4" - 38 15/16" - 54 5/16"	64 15/16" - 38 15/16" - 54 5/16"
	Inches-MM	1150 - 989 - 1380	1650 - 989 - 1380
Crated Dimensions (L-D-H)	Inches	54 1/3" - 46" - 63 1/4"	74" - 46" - 63 3/4"
	Inches-MM	1380 - 1168 - 1620	1880 - 1168 - 1620
Top Refrigeration Display Area	Type	Fan Ventilated	Fan Ventilated
Refrigeration Display Area	Type	Deck / Lower Shelf	Deck / Lower Shelf
Open Area & Top Deck			
Operating Temperature	°C / °F	+4°C / 39.2°F	+4°C / 39.2°F
Compressor	Nr./Type	1 / Hermetic	1 / Hermetic
Cooling Power @+10°C/+14°F	(W/BTU'S)	1350W / 4350BTU'S	1680W / 5320BTU'S
Electric Supply	(V/Ph/Hz)	230/1/50 (UE) 220/1/60 (USA)	230/1/50 (UE) 220/1/60 (USA)
Power Consumption	(A)	9A	13A
Defrost	Mode/Type	Electric	Electric
Climatic Class	N°/°C/°F°/H.R.	4+/35/95/70%	4+/35/95/70%
Refrigerant Gas	Type	R404A	R404A
Net Weights	Kg/Lb	266Kgs / 586Lbs	350Kgs / 771Lbs
Crated Weights	Kg/Lb	391Kgs / 862Lbs	525Kgs / 1157Lbs

* Dimensions are without side panels